





EB3FX/TT - Lincat
FilterFlow FX Countertop Automatic Fill TwinTemperature Water
Boiler - W 250 mm - 3.0
kW

The FilterFlow Automatic Water Boiler comes with a twin tank, allowing you to set two different temperatures for the perfect cup of tea.

- Twin tank model, tanks can be set to different temperatures - ideal for brewing black teas at 98°C and green teas at 71°C
- Lockable mode prevents water being dispensed without the input of a PIN code, perfect for schools, prisons, care homes and settings with vulnerable individuals
- Narrow 250mm footprint saves valuable counter space without compromising capacity or performance
- Built-in water filtration system improves water quality and reduces scale build-up. High volume, easy change FilterFlow cartridge

- Easily operated from a large, colour touchscreen display. Menu navigation is quick and easy with the temperature and timer simple to adjust
- Eco setting reduces the volume of boiling water by 50% for quieter periods. The intelligent predictive eco setting learns usage patterns and switches between eco mode and standard mode to deliver the required hot water output in the most economical way
- 7-day timer allows the boiler to be programmed to switch off overnight or at weekends to conserve energy
- Enhanced diagnostics identify possible causes. The on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit

## **Specifications** Summary **Power and Performance** Total Power kW **Brand** 3.0 Range FilterFlow Temperature Range °C 70-98 Series **IP Rating** IP23 FX Counter-top Boiler **Power Type Hourly Output Litres** 25 Electric **Unit Type** Counter-top **Hourly Output Cups** 125 Available in UK Only **Temperature Control** Electronic **UK Warranty** 2 Years Parts and Labour Warranty **Export Warranty** Contact your local dealer **GTIN** 5056105101390 **Key Specifications** Capacity **Hot and Cold Water Output** Outlet Twin Tap Nο Rapid Draw Off Litres Dispense Lock 2 x 4 5 No **WRAS Approved Rapid Draw Off Cups** 45 **Capacity Litres** 15.0





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	596	Requires Installation	No	
Unit Width (External) mm	250	Requires Electrical Supply	Yes	
Unit Depth (External) mm	525	UK 3 Pin Plug	Yes	
Net Weight Kg	17.1	Requires Hardwiring	No	
		Electrical Supply Rating Watts	3,000	
		Single Phase Amps	13	
		Single Phase Voltage	230	
		Water Connection Pressure Bar	6	
		Water Connection	3/4"	
			<i></i>	

## Shipping

Packed Weight Kg19.7Packed Height cm53Packed Width cm69.5Packed Depth cm36.6

## **Available Accessories**

**BR55** EB3FX AND EB4FX WALL BRACKET

**DP10** DESCALER POWDER

**EBHF01** Lincat EB Hands Free Tap Adaptor


**FC04** Filter Cartridge for Lincat FilterFlow Water Boiler


## **Technical Picture**













**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm